



FLEX SA PRIMER

PRODUCT DESCRIPTION

Flex SA Primer is an SBS primer designed to enhance the adhesion of Flex self-adhesive membranes on porous surfaces such as “DensGlass Gold” and “DensDeck” at temperatures above 14° F (-10°C). Flex SA Primer is comprised of a proprietary blend of SBS polymers, adhesive enhancing resins and solvents used to increase adhesion when using Flex SA vapor Barrier membrane. Flex SA Primer may be applied to gypsum, metal, wood and masonry substrates.

APPLICATION

Flex SA Primer is applied via brush or roller. It must be thoroughly dry before applying the waterproofing membrane. Flex SA Primer must be mixed well before use.

COVERAGE RATE

Average coverage : porous surfaces – .75 to 1.22 gal / 100 sqft. (0.3 to 0.5 L/m²)
Non-porous surfaces – .024 to .60 gal/100 sq ft. (0.1 to 0.25 L/m²)

PHYSICAL PROPERTIES

Specific Gravity at 68°F (20°C)	0.79 kg/L
Color	Red
Solids by Weight	24%
Viscosity, Brookfield at 77°F (25°C)	200 cP
Drying Time	15 to 60 minutes depending on temperature and quantity applied

PACKAGING

1 gal. (3.78 L) Pails – 5 gal. (19 L) Pails

STORAGE AND HANDLING

Shelf Life: Up to 60 months in original sealed containers, in cool and ventilated area. Store in pail and maintain in an upright position to prevent damage. Monitor varying environmental conditions during storage, handling and application of Flex SA Primer. Store in a well ventilated area. Keep away from any source of heat, dampness, humidity, oxidizing agents or direct sunlight. Flammable before curing. Keep away from sources of ignition. Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

WARNING

Do not accelerate drying of Flex SA Primer by heating it with a torch. For complete information on product installation, please consult your Flex Representative.

For additional information, refer to instruction on the label of the can and to relevant Safety Data Sheets (SDS).